



VAGANS 7

Product Description:

Vagans 7 is a silky matte, water based, styrene acrylic paint intended for walls and ceilings indoor. It is especially suited for top coating where a warm, silky matte surface is desired. Vagans 7 has high cover and richness. This paint is easily applied with a minimum of splash and provides a subdued, matte surface with a beautiful finish. High washability makes this paint suitable at home as well as in public environments. Suitable surfaces are concrete, plaster, fabrics, wall paper and earlier painted surfaces.

Vagans 7 is produced in Sweden, is included in Colorex Mix tinting system and Eco-labelled.

TECHNICAL DATA:

Area of application	Indoors
Binder	Styrene acrylic
Volume Solids	35%
Density	1,32 kg/l
Gloss	6–8 (matt)
Washability	Class 2 (EN 13300)
Thinner/Cleaning	Water
Material consumption	6–8 m ² /L
Temperature at painting	Minimum +5°C
Tools for painting	Brush, roller and spray
Dust dry	1 h
Re-paintable	2–3 h
Completely dry	24 h
Shelf life	2 years if unopened, frost free storage
Colour	White
Flammability	Not flammable
VOC category	(Cat A/a): 30 g/l (2010)



VAGANS 7

How to use:

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir the paint properly from the bottom before starting painting. Make sure that the foundation is clean, dry and free from dust before painting. Wash earlier painted surfaces with façade cleaner and rinse with water. Glossy surfaces – previous painted with acrylic paint – must be sanded matte before painting.

Protect floor and furniture properly before starting to paint.

Painting

Paint 1–2 times with roller, brush or – after dilution – by spraying for an even finish with full cover. Disturbing discrepancies in nuance will be avoided if you paint the coherent surfaces with paint from the same tin. This concerns especially tinted paint. When this is not possible, then use tins with same batch number, which can be read on the label. Since this paint has a fine structure in order to provide a smooth and forgiving surface, smooth the newly painted and still wet surface by pulling the roller in the same direction and with the same pressure and speed. The structure of the paint will then take the same direction, which will give a matte and soft surface without reflections. This will prevent that the light shines different on the surface and gives a mottled appearance.

Post-painting

Wipe off the tools thoroughly before cleaning with water. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

Maintenance

Be careful when cleaning surfaces with acrylic paint with lower gloss, since the paint has a more sensitive finish. Use a damp rag and possibly some mild cleaning liquid to clean the surface. Never use spirits when cleaning painted or lacquered surfaces. Resistant against normal household chemicals.