



Eminent Pro 2 RF

TECHNICAL PRODUCT DATA SHEET

2019-11-06

Page 1/2

PRODUCT DESCRIPTION

Eminent Pro 2 RF is a ceiling paint which, compared to similar products, has an extremely high coverage, high fillness and whiteness and is totally reflection free. It is intended to use as a top coat indoors, but works also very good as a primer coat. Suitable surfaces are ceilings of concrete, plaster, fiber board and gypsum board. This paint is an excellent choice also for machine painting with airless sprayer. The high solids content provides the paint extremely good coverage. The paint is easy to apply with a minimum of splash and provides a fully mat surface with a beautiful finish and no glossy appearance in raking light.

TECHNICAL DATA:

Area of application	Indoors
Binder	VAE
Volume Solids	32%
Density	1,40 kg/L
Gloss	1, fully matt (EN 13300)
Washability	Class 3 (EN 13300)
Thinner/Cleaning	Water
Material consumption	5–8 m ² /L
Temperature at painting	Minimum +5°C
Tools for painting	Brush, roller or spray
Dust dry	1 h
Re-paintable	2 h
Completely dry	24 h
Shelf life	2 years if unopened, frost free storage
Colour	White
Flammability	Not flammable
VOC category	(Cat. A/a): 30 g/l (2010)



Eminent Pro 2 RF

HOW TO USE

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a careful preparation is an important key for a successful result. Stir the paint properly from the bottom before starting to paint. Apply under controlled conditions, where air-, paint- and surface temperature may not be below +5°C. High humidity will prolong the drying time. The ceiling shall be clean, with good adhesion, dry and dust free. Wash, rinse and let dry well. Chalky basis, such as lime- and gluepainted surfaces should be washed and primed with suitable insulating sealer before painting. Protect floor and furniture properly before starting to paint.

Painting

To receive full cover we recommend two layers with paint. Apply with brush or suitable roller. After light diluting with water it can also be applied by spraying. The ceiling shall always be painted with a good deal of paint in the roller. This is to avoid splices and stripes. Paint the ceiling crosswise and the last coat always against the largest natural daylight. Paint the whole ceiling at the same time. Smoothen the newly painted and still wet surface in the ceiling by pulling the roller in the same direction and with the same pressure and speed. The structure of the paint will then take the same direction, which will give a matt and soft surface without reflections. The paint will reach it's full covering capabilities first when it is completely dry.

Post- painting

Wipe off the tools thoroughly before cleaning in water and a mild cleaning liquid. Seal the paint container carefully after use and keep out of reach for children. Liquid residues must not be poured down the drain, but be submitted to the local collection point.

Maintenance. Be careful when cleaning surfaces with acrylic paint with lower gloss, since the paint has a more sensitive finish. Use a damp rag and possibly some mild cleaning liquid to clean the surface. Never use spirits when cleaning painted or lacquered surfaces.