



MÄSTAR VARM

Product description:

Durable acrylic paint for painting radiators and metal parts indoors.

The product has high adhesion, opacity and provides a hard surface that does not turn into yellow by heat. Suitable for pipes and radiators not exceeding 80°C.

Not to be used on electric radiators. Mästar Varm is produced in Sweden.

TECHNICAL DATA:

Area of application	Indoors
Binder	Acrylic
Volume Solids	40%
Density	1,28 g/cm ³
Viscosity	280
Gloss	Semi glossy
Washability	Yes. > 10 000 cycles
Thinner/Cleaning	Water
Material consumption	7–10 m ² /L
Temperature at painting	Minimum +5°C
Tools for painting	Brush, enamel-roller and (after dilution) spray
Dust dry	1–2 h
Re-paintable	12 h
Shelf life	2 years in unopened tin, frostless storage
Colour	White
Flammability	Not flammable
VOC category	(Cat. A/c): 130 g/l (2010)



MÄSTAR VARM

How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before you start painting. The temperature of the room and surface is also important for the final result. Do not paint if it is below +5°C.

The surface has to be clean, dry and firm.

Any stains or surfaces where the metal is uncoated should be primed with suitable sealant, such as the Colorex Häftprimer.

Remember to protect floors and furniture properly before painting.

Painting

Apply on radiators that are turned off and that is no longer warmer than approximately 20°C.

Paint 1–2 times for full cover.

Post-painting

Wipe off the tools thoroughly before cleaning with water. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

Maintenance

Use a cloth dampened in water and possibly some mild cleaning liquid to clean the surface. Never use spirits when cleaning painted or lacquered surfaces.