



# Utegrund Classic

## Product description:

Utegrund Classic is a matte, traditional alkyd-based primer for exterior wooden surfaces. The paint has good penetration characteristics, and excellent adhesion and richness. The primer is suitable for all exterior wood paints.

Utegrund Classic is produced in Sweden.

## TECHNICAL DATA:

Area of application	Outdoors
Binder	Alkyd
Volume Solids	46%
Density	1,29 kg/l
Gloss	Fully matt
Washability	Class 1 (EN 13300)
Thinner/Cleaning	White spirit/Naphtha
Material consumption	4–7 m <sup>2</sup> /L sawn wood, 7–10 m <sup>2</sup> /L planed wood
Temperature at painting	Minimum +5°C
Tools for painting	Brush, roller and sprayer
Dust dry	4 h
Re-paintable	16-24 h
Completely dry	Several days
Shelf life	2 years if unopened, frost free storage
Colour	White
Flammability	3
VOC category	(Cat. A/d): 300 g/l (2010)



# Utegrund Classic

## How to use

### Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint. The air and surface temperature is also important for the end result. Do not paint if it is below +5°C.

The surface must be clean, dry and firm. Brush or scrape off loose old paint and/or porous and degraded wood. Wash previously painted surfaces with appropriate cleaner. Rinse with water and let dry.

Before priming it is preferable to use Grundolja Classic, especially when it comes to end grains and wood joints.

### Painting

Apply one or two coats. The first layer – diluted with 5% Naphta – can be used for more intense penetration. Apply preferably several thin coats – with a day or two to dry in between – then a few thicker coats. Wood not previous treated, two coats is to recommend. Avoid painting on warm and sunlit surfaces. When the primer is completely dry, use one of our top coats for outdoors, for instance Storm, Solid or Titan.

### Post-painting

Wipe off the tools thoroughly before cleaning with white spirit. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.