



Röde orm Classic red Paint

Röde orm is a Swedish made, water based paint for new, unplanned timber, or repainting of wood surfaced previously painted with distemper.

Röde orm is intended for outdoors and has a matt appearance.

The paint does not create a dense layer which prevents moisture to pass through. The wood is therefore able to breath and the risk of rot and mould formation is reduced.

Röde orm contains anti-mould agent but no lead compounds.

Pre-painting

- Cover the foundations, gutters and windows with protective paper or plastic.
- Brush the façade clean from dirt and loose pigments with a broom or wire brush. Finish off with a soft brush.
- Prime with Röde Orm, diluted with approx. 20% water.
- If there is a risk of mould spores in the wood, use an appropriate detergent as first treatment.

Painting

- New wood: Wait at least 24 hours before applying the final coat of undiluted Röde orm.
- Re-painting: Apply undiluted Röde Orm. If it is necessary with two coats when re-painting, the first coat shall be diluted with at least 20% water. Apply as thin as possible until sufficient cover.
- Do not paint sunlit surfaces. The paint will otherwise dry too fast which can result in flakes. Do not paint when it is below +5°C, or if there is a risk of night frost.
- On nails, knots and resin-rich areas the paint may have difficulties to attach. These surfaces can be ruffled with a course sand paper.
- If peeling occurs, scrape off the flakes and re-paint with diluted paint.
- Stir the paint well from the bottom when needed.
- Always apply the paint thinly with a robust brush, do not use roller.

Post painting

- Wipe off the tools thoroughly before cleaning with water. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, we do.

Technical data			
Use	Outdoors	Class of flammability	Not flammable
Binder	Boiled linseed oil	Storage time	2 years if unopened, frost free storage
Gloss	Matt	Air/surface temperature by painting	Minimum +5°C
VOC-Category	(Cat. A/d): 130 g/l (2010)	Consumption	2–3 m ² /L.
Cleaning of tools	Water	Application	Brush
Dilution	Water	Package	10 L.
Drying time	1 hour dust dry	In stock	Yes
(depending on air/surface temp.)	4 hours re-paintable		
	24–48 hours fully hardened		



The information in this data sheet is based on laboratory tests and practical experience. Since the conditions, under which the product is used, are beyond our control, we can only guarantee the quality of the product itself. The end-result depends on the surface, preparation, temperature, humidity and execution etc.

Please check our web site to make sure that this Product data sheet is valid.