



Trogen Window Paint

Trogen is a glossy, solvent based alkyd paint, specifically made for painting windows and different carpentry outdoors.

Trogen is easy to apply, with high opacity and high flexibility, which gives a good result on sharp edges. Trogen is persistent and highly water repellent. Provides protection against mould.

This product is produced in Sweden and included in the Colorex Mix tinting system.

Pre-painting

- Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint.
- The use of correct tools and a carefully performed base is the foundation for a successful result. Do not paint if it is below +5°C.
- The surface must be clean, dry and firm. Brush or scrape off loose, old paint. Wash previously painted surfaces with appropriate cleaner and rinse with water.
- Before priming, the surfaces should be oiled with Grund I Klassisk primer oil. Pay special attention to end grain and timber joints.
- Prime new and previous unpainted surfaces with Grund II Klassisk outdoor primer. Hard or resin rich wood should be primed with Grund II Klassisk diluted by 10–15% white spirit

Application

- Apply two thin coats and allow a drying time for a day or two. Avoid painting on warm and sunlit surfaces.

Post-painting

- Wipe off the tools thoroughly before cleaning with white spirit. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, we do.

Maintenance

- Use a damp cloth and if necessary some mild detergent to clean the surface.
- Properly executed system painting with Grund I Klassisk, Grund II Klassisk and Trogen gives a maintenance free area for many years.

Technical data

Use	Outdoors	Class of flammability	3
Binder	Alkyd	Storage time	2 years if unopened, frost free storage
Gloss	60 (glossy)	Air/surface temperature by painting	Minimum +5°C
VOC-Category	(Cat. A/d): 300 g/l (2010)	Cover	6–10 m ² /L.
Cleaning of tools	White spirit/Naphtha	Application tools	Brush, enamel-roller and (after dilution) spray
Dilution	White spirit/ Naphtha	Package	0.9 and 2.7 Litres
Drying time	8–10 hours dust dry	In stock	Yes
(depending on air/surface temp)	16–32 hours re-paintable		

The data above are valid for white/unmodified paint. When modified, technical data can vary.



The information in this data sheet is based on laboratory tests and practical experience. Since the conditions, under which the product is used, are beyond our control, we can only guarantee the quality of the product itself. The end-result depends on the surface, preparation, temperature, humidity and execution etc.

Please check our web site to make sure that this Product data sheet is valid.