



TECHNICAL PRODUCT DATA SHEET

2019-08-07

Page 1/2

Product description:

Klassisk 30 is a traditional oil, intended for treatment of new, earlier untreated wood, as well as pressure-treated and earlier stained wood outdoors. The product protects the foundation against dehydration, cracking and discoloration.

Intended for untreated or oiled woods – planed or sawn – outdoors. Suitable upon wooden terraces, carpentry, furniture, fences, boats, etc.

Klassisk 30 is produced in Sweden.

TECHNICAL DATA:

Area of application Outdoors

Binder Linseed oil /alkyd

Volume Solids 31%

Density 0,84 kg/l

Gloss Dependent on surface Thinner/Cleaning White spirit/naphtha

Material consumption 4–12 m²/L

Temperature at painting Minimum +5°C

Tools for painting Brush, sponge or cloth

Dust dry 6 h
Re-paintable 24 h

Completely dry 48-72 h

Shelf life 2 years if unopened, frost free

storage

Colour Clear

Flammability Not flammable

VOC category (Cat. A/f): 700 g/l (2010)

Hagmans Nordic AB Industrigatan 7, 534 73 Stora Levene Telefon: 0512 18 00 00

info@colorex.se

Version: 2019-08-01 09:24





Version: 2019-08-01 09:24

TECHNICAL PRODUCT DATA SHEET

2019-08-07

Page 2/2

How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint. The air and surface temperature is also important for the end result. Do not paint if it is below +5°C. The surface must be clean, dry and firm. Brush or scrape off loose old paint and/or porous and degraded wood. Wash and rinse with water and let dry.

Painting

The oil is to be thoroughly penetrating the material until the surface stops to absorb the oil. Wait a few minutes and then wipe off excess oil with a cloth or a sponge. Treat the whole surface of a board simultaneously to avoid overlapping.

Be extra careful when it comes to end grains and timber joints.

Post-painting

Wipe off the tools thoroughly before cleaning with white spirit. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

N.B.! Cloths soaked in oil may spontaneously combust and must therefore be neutralised.

Maintenance

It is good to repeat the treatment a couple of times pro year, especially in the autumn.