



Finspackel LF

Product description:

Finspackel LF is water-borne fine putty based on copolymer.

Range of use: Finspackel LF is suitable for putty work on plaster board, woven fabrics, old wallpaper etc. Especially characterized by its excellent surface finish.

Finspackel LF fulfil the demands for CE marking according to EN 15824:2009 and EN 13963:2005

TECHNICAL DATA:

Colour	White
Solvent	water
Filling capability	3mm
Grain size	max. 0,12 mm
Dry substance	ca 62 %
Density	ca 1 200 kg/m ³
Application	manually
Drying time	1 hour per mm, longer for thicker layers
Adherence	the product has a high tack against concrete and plaster
Temperature of use	+5°C - +35°C
Cleaning of tools	water
Remarks	when sandpapering putty, use eye-protection and a face protective mask



Finspackel LF

TECHNICAL PRODUCT DATA SHEET

2019-05-07

Page 2/2

WORKING INSTRUCTIONS

Prepare the basis before bonding so that it becomes even and firm. Important that the temperature on surface not will be lower than +5°C.

Use a steel spatula for applied the putty. The drying time can vary depending on the base, temperature, air humidity etc.

When sandpapering putty, use eye-protection and a face protective mask. The grounded surface shall be dusted before further processing such as painting and wallpapering done.

If the surface will be wallpapered it should be primed, see also the directions given by the wallpaper manufacturer.

For cleaning of tools use lukewarm water before the putty has dried.

