Snickerispackel

Product description

COLOREX SNICKERISPACKEL is water-based, very fine-grade filler with good colour bearing capacity.
Range of use; COLOREX SNICKERISPACKEL is good for filling on wood and carpentry work.
The filler has good open-time and suites for that reason for filling of bigger areas, like width filling of door-blades.

TECHNICAL DATA:

Colour	white
Solvent	water
Grain size	max 0,030 mm
Density	approx. 1 700 kg/m3
Dry substance	approx. 74 %
Application	Apply by hand with a wide-putty knife or a Japanese-putty knife.
Drying time	Appr. 1 hour at 1 mm layer. Drying period depends on foundation, temperature, air humidity etc
Adhesion	the product has good adhesion to wood
Material consumption	1 litre/m² at 1 mm layer. Depends much on foundations character.
Application temperature	+5 - +35°C
Cleaning of tools	water

Hagmans Nordic AB
Industrigatan 7, 534 73 Stora Levene
Telefon: 0512 18 00 00
info@colorex.se

Snickerispackel

WORKING INSTRUCTIONS

Prepare the basis before bonding so that it becomes even and firm. Important that the surface temperature is not less than +5°C.
Use a steel spatula for applied the putty. The drying time can vary depending on the base, temperature, air humidity etc.
When sandpapering putty, use eye-protection and a face protective mask. The grounded surface shall be dusted before further processing such as painting and wallpapering done.
If the surface will be painted see the directions given by the paint manufacturer.
For cleaning of tools use lukewarm water before the putty has dried.

Hagmans Nordic AB
Industrigatan 7, 534 73 Stora Levene
Telefon: 0512 18 00 00
info@colorex.se