Identification number: 11541601-001



Declaration of Performance Latexfog

| Unique ID-code for type of product: | Latexfog | |
|---|---|--|
| Building product's intended use: | Sealing of joints in interior applications according to EN 15651-1:2012, Typ F INT. | |
| Name of manufacturer: | Hagmans Nordic AB Förläggarevägen 2, Box 112 511 10 Fritsla Sweden | |
| The system or systems for the assessment and continuous control of the building product's performance, according to appendix V: | System 4 | |
| In those cases where the declaration of performance is for a building product embodied by a harmonized standard | EN 15651-1:2012, Typ F INT. | |

Declared performance

| Important properties | Performance | Teststandard | Harmonized technical specification |
|----------------------|-------------|--------------|------------------------------------|
| Reaction to Fire | E | EN 13501-1 | EN 15651-1:2012, Typ F |
| Resistance to flow | ≤ 5 mm | EN ISO 7390 | INT |
| Loss of volume | ≤ 45 % | EN ISO 10563 | |
| Tensile properties | ≥ 25 % | EN ISO 8339 | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed by the manufacturer of:

Camilla Eliasson, R&D Manager-Fritsla

Fritsla, 2018-04-12