

Colorex

BLOCKA



Product description:

Blocka is a matt, alkyd based sealer with high washability, primarily intended for use as insulation paint. Blocka is also suitable as primer and top coat on walls indoors.

The product is versatile everywhere when a washable, fully matt surface is desired on surfaces of wood, concrete, plaster, chip- and fibreboard etc.

The product also blocks strong odours from walls and ceilings.

Blocka is also very convenient for repainting previous distempered or lime washed surfaces where water-borne materials not are suitable.

The paint has very high coverage and richness. It provides a fully matt surface with low light reflection.

As solvent isoparaffin is used, this is almost completely odourless, even when working indoors.

Blocka is produced in Sweden.

TECHNICAL DATA:

Area of application	Out-/Indoors
Binder	Alkyd
Volume Solids	53%
Weight Solids	76%
Density	1,50 kg/l
Gloss	3 (fully matt)
Washability	Class 1 (EN 13300)
Thinner/Cleaning	White spirit/Naphtha
Material consumption	4–6 m ² /L
Temperature at painting	Minimum +5°C
Tools for painting	Brush, roller and (after diluting) sprayer
Dust dry	6 h
Re-paintable	48 h
Completely dry	72 h
Colour	White
Flammability	3
VOC category	(Cat. A/g): 350 g/l (2010)

Colorex

BLOCKA



How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint.

The air and surface temperature is also important for the end result. Do not paint if it is below +5°C. The surface must be clean, firm, dry and dust free. Brush or scrape away loose old paint. Previously glossy surfaces need to be sanded.

Protect floor and furniture properly before starting to paint.

Painting

The product is ready to use. Apply with roller or brush. After diluting with white spirit (preferable aromatic free) spraying is also possible. When used for isolation of knots, we recommend using brush. Since the paint has a certain structure to give an even and concealing surface, it is necessary to smoothen the surface. When painting for instance a ceiling, as the paint is spread on the surface, pull the roller in the same direction, with the same pressure and speed, in the still wet paint. All peaks will then be equivalent. Thereby is avoided that the light is reflected differently, which can give a patchy appearance.

The same paint is used as primer as well as top coat. Normally one coat is sufficient, but in some situations two layers, with drying time in between, can be necessary.

Surfaces with many knots often require – achieving the best insulation – the first application to be one thin coat of Blocka. Let dry at least 14–18 hours, and apply one more coat.

Post-painting

Wipe off the tools thoroughly before cleaning with white spirit. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

Maintenance

High washability with high resistance against normal household chemicals.