



PRODUCT DESCRIPTION

Vagans Pro+ 4 is a pro adapted waterborne acrylic paint with a high opacity, whiteness and non-existent odor and emission to the environment in connection with drying. It is primarily designed for interior painting of walls and ceiling on concrete, plaster, fibre boards, wallpaper or previously painted surfaces. It can also be used as primer on highly absorbent substrates. Vagans Pro+ 4 is an excellent choice for machine painting. The high solids content gives the colour extremely high opacity. The product has excellent application properties and is easy to apply to a smooth surface with minimal roller splashing. Vagans Pro+ 4 provides a washable, durable and matt surface. The product is produced in Sweden, and is included in the Colorex Mix tinting system.

TECHNICAL DATA:

PARAMETER	VALUE	UNIT	METHOD
Area of application	Indoor		
Binder	Acrylic		
Volume Solids	40%		
Weight Solids	57%		
Density	1,40	kg/l	ISO 12 185
Gloss	4 (fully matt)		
Spreading rate	8,9 (RAL 9010)	m ² /l	EN 13300
Hiding power	Class 1		EN 13300
Material consumption	7-9	m ² /l	
Washability	Class 1		EN 13300
Thinner/Cleaning	Water		
Temperature at painting	Minimum +5°C		
Tools for painting	Brush, roller and spray		
Dust dry	1 h		
Re-paintable	2–3 h		
Completely dry	24 h		
Colour	White		
Flammability	Not flammable		
VOC category	<3 g/l (Cat. A/a)		



HOW TO USE

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a careful preparation is an important key for a successful result. Stir the paint properly from the bottom before starting painting to paint. Room and surface temperature is important too for the end result. Do not paint if it is below +5°C. The object which will be painted shall be clean, with good adhesion, dry and dust free. Wash, rinse and remove old paint with bad adhesion. Prime with suitable primer before painting chalky surfaces, such as distemper. Protect floors and furniture thoroughly before beginning to paint.

Painting

Paint at least twice for full coverage with a roller, brush, or – after dilution – with sprayer. Ceilings should always be painted with a lot of paint in the roller to avoid seams and stripes. Always paint the ceiling in different directions, but with the final coat in the source of light direction.

Post-painting

Wipe off the tools thoroughly before cleaning with water. Seal the paint container carefully after use and keep out of reach for children. Liquid residues must not be poured down the drain, but be submitted to the local collection point.

Maintenance

Use a cloth dampened in water and possibly some mild cleaning liquid to clean the surface. Never use spirits when cleaning painted or lacquered surfaces.