



Adhesion Primer Aqua

Product description:

Adhesion Primer Aqua is a fast drying, waterborne alkyd-based primer that is easy to apply, for wood and metal surfaces. The paint is intended to be used as primer against corrosion and bleeding through on all types of surfaces, indoors as well as outdoors. Adhesion Primer Aqua can be applied on both new and previously painted surfaces of wood, fibreboard, drywall, metal, tiles, glass, etc.

TECHNICAL DATA:

How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint. The air and surface temperature is also important for the end result. Do not paint if it is below +5°C. Remember to protect floors and furniture thoroughly before beginning to paint. The surface must be thoroughly cleaned, steel brushed or sand blasted.

Painting

Apply Häftprimer by brush or roller. After dilution with 5–10% water it is possible to use sprayer as well.

Make sure that the foundation, for instance previous painted surface, has good adhesion. Apply in thin coats, usually two, but it will be decided by the surface.

Post-painting

Wipe off the tools thoroughly before cleaning in water. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.