



## Eminent 2

### Product description:

Eminent 2 is a completely matt, waterborne paint with very high cover and richness. It is intended for prime- and top coating of ceilings indoors in dry areas.

This paint is especially customized for those demands that are required, such as non-splashing application and a matt, non-reflecting surface with very low structure.

Eminent 2 is also suitable as primer underneath wall paint with higher gloss and upon glass fibre fabrics. The product is included in ColorexMix tinting system.

### TECHNICAL DATA:

PARAMETER	VALUE	UNIT	METHOD
Area of application	Indoors		
Binder	VAE		
Density	1,51 kg/L		
Viscosity	146 cP		
Gloss	2-3 (fully matt)		
Washability	Class 4 (EN 13300)		
Thinner/Cleaning	Water		
Material consumption	4–8 m <sup>2</sup> /L		
Temperature at painting	Minimum +5°C		
Tools for painting	Brush, roller and spray		
Dust dry	1 h		
Re-paintable	2 h		
Completely dry	12 h		
Shelf life	2 years if unopened, frost free storage		
Colour	White		
Flammability	Not flammable		
VOC category	(Cat. A/a): 15 g/l (2010)		

# Colorex

## Eminent 2



### HOW TO USE

#### Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a careful preparation is an important key for a successful result. Stir the paint properly from the bottom before starting to paint. Apply under controlled conditions, where air-, paint- and surface temperature may not be below +5°C. High humidity will prolong the drying time. The ceiling shall be clean, with good adhesion, dry and dust free. Wash, rinse and let dry well. Chalky basis, such as lime- and gluepainted surfaces should be washed and primed with alkyd-sealer before painting. Protect floor and furniture properly before starting to paint.

#### Painting

To receive full cover we recommend two layers with paint. Apply with brush or suitable roller. After light diluting with water it can also be applied by spraying. The ceiling shall always be painted with a good deal of paint in the roller. This is to avoid splices and stripes. Paint the ceiling crosswise and the last coat always against the largest natural daylight. Paint the whole ceiling at the same time. Smoothen the newly painted and still wet surface in the ceiling by pulling the roller in the same direction and with the same pressure and speed. The structure of the paint will then take the same direction, which will give a matt and soft surface without reflections.

#### Post- painting

Wipe off the tools thoroughly before cleaning in water and a mild cleaning liquid. Seal the paint container carefully after use and keep out of reach for children. Liquid residues must not be poured down the drain, but be submitted to the local collection point.

#### Maintenance

Be careful when cleaning surfaces with acrylic paint with lower gloss, since the paint has a more sensitive finish. Use a damp rag and possibly some mild cleaning liquid to clean the surface. Never use spirits when cleaning painted or lacquered surfaces.