



Fokus V Woodstain

Product description:

Fokus V Woodstain is a semi matt; water based wood and transparent wood preservative. This product is based on a combination of alkyd oil and acrylate. The product is intended for previously untreated or oiled wood, planed or sawn, indoors as well as outdoors. The product is particularly well adapted for log homes. It provides a transparent effect that accentuates the wood structure. On horizontal surfaces, such as terraces with high wear and tear, we rather recommended Proper decking stain.

Fokus V Woodstain has a high water resistance and delays the negative effects of moisture and UV light on the timber. Contains mould protection. The product is ready to use and should not be diluted.

The product is primarily intended to be shaded in any of our colours, or tinted to the desired stain nuance.

Fokus V Woodstain is produced in Sweden and is included in Colorex Mix tinting system.

TECHNICAL DATA:

Area of application	Out-/Indoors
Binder	Alkyd/acrylate
Volume Solids	20%
Density	1,02 kg/l
Gloss	Semi matt
Thinner/Cleaning	Water
Material consumption	5–12 m ² /L
Temperature at painting	Minimum +5°C
Tools for painting	Brush
Dust dry	6 h
Re-paintable	12 h
Colour	White
Flammability	Not flammable
VOC category	(Cat. A/e): 130 g/l (2010)



Fokus V Woodstain

How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint. Old, well scraped surfaces are to be washed with a suitable cleaning, rinse with water and let dry well. In case of fungal attack, the surface should be treated with appropriate germicidal liquid.

Painting

Apply with dense brush, and work the stain into the timber. Be especially careful to treat end grain and timber joints. These surfaces should first be primed with Grundolja Aqua - H2O primer oil.

N.B.! Keep in mind that the colour gets darker if more layers are applied. Avoid double coats. Apply boards throughout, without overlapping, to obtain a uniform shade.

If a lighter nuance is desired, prime first with Fokus without pigment. Avoid painting hot and sunlit surfaces.

Post-painting

Wipe off the tools thoroughly before cleaning with water and some mild detergent solution. Seal the tin carefully after use and keep out of reach for children.

Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

Maintenance

Can be cleaned with a soft scrub brush and if needed a mild detergent solution.