



Gard V Woodoil

Product description:

Gard V Woodoil is a Swedish made, environmentally friendly and waterborne wood oil for applying on untreated, or previously oiled wood, outdoors. The product is suitable for maintenance of garden furniture, decks, windows, façades and joinery. It is based upon natural special oils which

provide a highly water-repellent surface. Gard V Woodoil is not intended as primer and application with paint afterwards is not possible. For this purpose we recommend Grund I Classic primer.

Since this product contains fungicides to prevent from mould, it is not to be used on surfaces which can be in direct contact with food.

TECHNICAL DATA:

Area of application	Outdoors
Binder	Specially selected natural oils
Density	1,01 kg/l
Gloss	Dependent on surface
Thinner/Cleaning	Water
Material consumption	5–15 m ² /L
Temperature at painting	Minimum +5°C
Tools for painting	Brush, sponge or cloth
Dust dry	2-4 h
Re-paintable	24-36 h
Completely dry	Several days
Colour	Clear
Flammability	Not flammable
VOC category	Cat. (A/f): 130 g/l (2010)



Gard V Woodoil

How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint. The air and surface temperature is also important for the end result. Do not paint if it is below +5°C.

The surface must be clean, dry and firm. Brush or scrape off loose old paint and/or porous and degraded wood. If the surface is contaminated with mould, it should be treated with appropriate detergent.

Painting

The oil is to be thoroughly penetrating the material until the surface stops to absorb the oil. Treat entire boards, avoid to overlap. Wait a few minutes and then wipe off excess oil with a cloth or a sponge. The oil is supposed to penetrate into the surface, not form a film on top.

Post-painting

Wipe off the tools thoroughly before cleaning with water and some detergent. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

N.B.! Cloths soaked in oil may spontaneously combust and must therefore be neutralised.

Maintenance

Repeat the treatment when the surface appears to be dry. Sunlit and not fully absorbed wood may need treatment a couple of times pro year.