



Prima V Decking stain

Product description:

Prima V Decking stain is a penetrating, alkyd based wood stain for treatment of wooden surfaces outdoors. Its high content of vegetable oils provides the surface a deep lustre. Prevents the wood from cracking and drying. Prima V Decking stain is a semi-matt, transparent, waterborne alkyd oil / acrylate-based wood stain for previously untreated or oiled wood, planed and sawn, outdoors. Particularly well suited for treatment of terraces in both untreated and impregnated wood. Prima V Decking stain is primarily intended to be shaded in any of our colours, or tinted to the desired stain nuance. Tinting gives the product increased protection against UV-radiation.

The stain contains the biocides DCOIT and OIT which protects the paint film against mould. The product has high UV resistance as well as water resistance.

Prima V Decking stain is produced in Sweden and included in Colorex Mix tinting system.

TECHNICAL DATA:

Area of application	Outdoor
Binder	Alkyd based oil
Volume Solids	23%
Density	1,02 kg/l
Thinner/Cleaning	Water
Material consumption	5–10 m ² /L
Temperature at painting	Minimum +5°C
Tools for painting	Brush, dipping or cloth
Colour	Clear
Flammability	3
VOC category	(Cat. A/f): 130 g/l (2010)



Prima V Decking stain

How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint. The surface must be clean, dry and firm. Scrape off loose, porous and degraded wood. Wash previously painted surfaces with appropriate cleaning and disinfect mouldy surfaces.

Prime new wood, end grains and timber joints with Grundolja Aqua- H2O Primer.

Painting

Apply the stain lengthwise by brush, cloth or by dipping until the surface is saturated. Wait a few minutes and then wipe off excess stain with a cloth or a sponge. The stain is supposed to penetrate into the surface, not form a film on top. Apply 1–2 layers. Keep in mind that the colour gets darker if more layers are applied. Apply boards throughout, without overlapping, to obtain a uniform shade. Avoid painting when there is a risk of sustaining rain and high humidity. Avoid painting hot and sunlit surfaces. The high dry content makes that Prima is not suitable as primer when coating with paint.

Post-painting

Wipe off the tools thoroughly before cleaning with water. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

N.B.! Cloths soaked in oil may spontaneously combust and must therefore be neutralised.

Maintenance

When necessary the surface can be cleaned with a soft scrub brush and possibly a little mild detergent solution.