

Colorex

Pro Primer



Product Description:

Pro Primer is intended for priming highly absorbing surfaces indoors, such as plaster, concrete, wood fibre boards and fibre glass. The product is less suitable for jute fabrics and sea grass wallpaper. Pro Primer carries the top coat layers in an excellent way, has very good surface adhesion and help to make joints and fillings even.

The product is suitable as primer on most surfaces; beneath wall paint that is glossier and before hanging wall papers.

TECHNICAL DATA:

Area of application	Indoors
Binder	VAE
Volume Solids	37%
Weight Solids	58%
Density	1,43 kg/l
Viscosity	180cp
Gloss	2–3 (fully matt)
Thinner/Cleaning	Water
Material consumption	5–9 m ² /L
Temperature at painting	Minimum. +5°C
Tools for painting	Brush, roller and spray
Dust dry	1 h
Re-paintable	2–3 h
Completely dry	24 h
Colour	White
Flammability	Not flammable
VOC category	(Cat. A/a): 30 g/l (2010)

Colorex

Pro Primer



TECHNICAL PRODUCT DATA SHEET

2022-10-26

Page 2/2

HOW TO USE

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint.

The use of correct tools and a carefully performed base is the foundation for a successful result. Do not paint if it is below +5°C. Make sure to protect floors and furniture before starting to paint. The surface must be clean, dry and firm.

Wash previous painted surfaces with paint washing liquid and rinse with water. Chalky bases, as distempred ceilings, should be washed and thereafter primed with Blocka sealer before painting.

Painting

Apply 1–2 times with roller, brush or – after dilution – with sprayer to achieve full cover. Since the product has high dry solid contents it provides very good cover ability. Pro Grund is the correct product to use when it comes to avoiding a variety of gloss when the surface differs in quality and structure.

Post-painting

Wipe off the tools thoroughly before cleaning with water. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

Maintenance

Use a cloth dampened in water and possibly some mild cleaning liquid to clean the surface. Never use spirits when cleaning painted or lacquered surfaces.