

## Roll filler coarse



### PRODUCT DESCRIPTION:

Roll filler Coarse is a waterborne all-round putty based on copolymer. The product is coarse-grained and has a low density and high filling capacity. The putty's consistency is adapted for roller application. The product is used indoors in dry spaces for roller application of walls and ceilings made of plaster, concrete, lightweight concrete, plasterboard, etc.

### TECHNICAL DATA:

Colour	light grey
Solvent	water
Filling capacity	max 6 mm
Density	ca 1,0 kg/L
Weight dry content	ca 62 %
Application	roller or putty shovel
Drying time	1 hour per mm
Using temp	+10°C - +25°C
Cleaning off tools	water
Storing	max. 12 month
Other	use protection glasses and mouthprotection when grinding



### INSTRUCTIONS FOR USE

The substrate must be dry, clean and well bound. It is important that the surface temperature is not lower than +10°C!

The putty is applied with a long-haired roller, or wide putty.

The drying time is affected by layer thickness, temperature, humidity, substrate etc.

Safety glasses and a respirator should be used when grinding. The sanded surface must be dusted off before further treatment such as painting and wallpapering takes place.

If the surface is to be wallpapered, the surface should be pre-glued, follow the wallpaper manufacturer's recommendations.

Tools are cleaned after use with water.

### Disclaimer

The data provided above, as well as our instructions and recommendations, are based on experience and a lot of trials.

They are intended to help our customers find the most suitable work method and as a guide when choosing a product.

As the consumer's working conditions are beyond our control, we cannot assume any responsibility for the results he obtains when using the product.