

Colorex

STORM



Product description:

Storm is a semi-matte acrylic paint for outdoor wood. It is very universal in its field of application and is suitable for most surfaces and substrates of wood, but it also works well on galvanized or previously painted outdoor plates.

Distinctive to Storm is the superior resistance to UV radiation, which keeps its shine and color and provides a beautiful and maintenance-free surface for many years. It also has a great flexibility that resists weather changes, even in a tough climate. The protection against molding of mold and algae is also very good. Storm is suitable for new wood as well as ground-based system with Grundolja Aqua and Utegrund Aqua or previously painted wood with oil paint or acrylate. Storm is ideal for painting all types of vertical wood surfaces outdoors, such as facade, carport and storage.

Not recommended for large horizontal surfaces of wood

TECHNICAL DATA:

Area of application	Outdoors
Binder	Acrylic
Volume Solids	36%
Density	1,21 g/cm ³
Viscosity	160
Gloss	20 (semi matt)
Thinner/Cleaning	Water
Material consumption	4–8 m ² /L
Temperature at painting	Minimum. +5°C
Tools for painting	Brush, roller and (after dilution) spray
Dust dry	2–4 h
Re-paintable	24–32 h
Completely dry	12–24 h
Colour	White
Flammability	Not flammable
VOC category	(Cat. A/d): 130 g/l (2010)

Colorex

STORM



How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint. The use of correct tools and a carefully performed base is the foundation for a successful result. Do not paint if it is below +5°C. The surface must be clean, dry and firm. Scrape off any loose old paint. Wash previously-painted surfaces with façade cleaner and disinfect mouldy surfaces.

Prime end grain, timber joints and new timber with Grundolja Aqua and Utegrund Aqua. Rough, sawn wood ought to be primed with two layers. Prime new or ground sheet metal surfaces with Sköld acrylic anticorrosive primer. Take care with the preparatory work and let the primer dry thoroughly.

Painting

Apply in several thin coats, allowing drying in between. When it comes to not previous painted surfaces, we recommend at least two layers. Do not paint during prolonged periods of cold or wet weather, and avoid painting hot or sunlit surfaces.

Post-painting

Wipe off the tools thoroughly before cleaning with water and a mild detergent. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

Maintenance

Surfaces painted with this product can be washed with appropriate façade detergents. Avoid strong alkaline cleaners; they may have negative effects on the surface, for example, loss of brightness.