

## PRODUCT DESCRIPTION


**Vagans Pro 20** is a durable styrene acrylic paint with high opacity and whiteness for professional use. Vagans Pro 20 is primarily intended for internal painting of walls in dry rooms where the highest demands are made on washability and durability. For example, public furnishings such as shops, offices, schools, hospitals, but also a home environment with high standards like kitchen and hall. Applies to most substrates of concrete, plaster, plaster and fiberboard, wallpaper, fiberglass or previously painted surfaces.

Vagans Pro 20 has high cover and richness. The paint is easily coated with a minimum of splash and provides a semi mat surface with a beautiful finish.

Vagans Pro 20 is produced in Sweden and included in Hagmans Nordic tinting system.

## TECHNICAL DATA:

Area of application	Indoor
Binder	Styrene acrylic
Volume Solids	38%
Density	1,27
Gloss	Semi matt
Washability	Class 1
Thinner/Cleaning	Water
Material consumption	7–9
Temperature at painting	Minimum +5°C
Tools for painting	Brush, roller and spray
Dust dry	1 h
Re-paintable	2-3 h
Completely dry	24 h
Colour	White
Flammability	Not flammable
VOC category	(Cat. A/a): <30 g/l



## HOW TO USE

### Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a careful preparation is an important key for a successful result. Stir the paint properly from the bottom before starting painting to paint. Room and surface temperature is important too for the end result. Do not paint if it is below +5°C. The object which will be painted shall be clean, with good adhesion, dry and dust free. Wash, flush and remove old paint with bad adhesion. Prime with suitable primer before painting chalky surfaces, such as distemper. Protect floors and furniture thoroughly before beginning to paint.

### Painting

Paint at least twice for full coverage with a roller, brush, or – after dilution – with sprayer. The high solids content gives the colour very high opacity. The product has excellent application properties and is easy to apply to a smooth surface with a minimum of roller splashing.

### Post-painting

Wipe off the tools thoroughly before cleaning with water. Seal the paint container carefully after use and keep out of reach for children. Liquid residues must not be poured down the drain, but be submitted to the local collection point.

### Maintenance

Use a cloth dampened in water and possibly some mild cleaning liquid to clean the surface. Never use spirits when cleaning painted or lacquered surfaces.