

## Titan Door & Window paint

### Product description:

Titan door and window-paint is a semi-glossy acrylate based paint, especially intended for windows and carpentry outdoors. The paint is easy to apply, with high coverage and it does not get sticky. This product provides a weather-resistant surface with good colour durability. The product's outstanding feature is the very good resistance to UV radiation, which keeps its shine and color and provides a beautiful and maintenance-free surface for many years. Titan door and window-paint is suitable for new wood as well as basic measurements in systems of basic oil and soil or wood surfaces previously painted with oil paint. Titan door and window-paint is produced in Sweden and included in the Colorex Mix tinting system.

### TECHNICAL DATA:

Area of application	Outdoors
Binder	Acrylic
Volume Solids	40%
Density	1,23 kg/l
Gloss	Half glossy (35)
Thinner/Cleaning	Water
Material consumption	6–8 m <sup>2</sup> /L.
Temperature at painting	Minimum. +5°C
Tools for painting	Brush, enamel-roller and (after dilution) spray
Dust dry	2 h
Re-paintable	6-8 h
Completely dry	48 h
Colour	White
Flammability	Not flammable
VOC category	(Cat. A/d): 130 g/l (2010)

## Titan Door & Window paint

### How to use

#### Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint. The use of correct tools and a carefully performed base is the foundation for a successful result. Do not paint if it is below +5°C. The surface must be clean, dry and firm. Brush or scrape away loose old paint. Wash previously painted surfaces appropriate cleaner and rinse with water.

Before priming, the surfaces should be oiled with Grundolja Aqua- primer oil. Pay special attention to end grain and timber joints.

Prime new and previous unpainted surfaces with Utegrund Aqua- outdoor primer.

#### Painting

Apply two thin coats and allow drying minimum 12 hours in between. Avoid painting on warm and sunlit surfaces or at the risk of rain/dew within 4–6 hours after completed painting. To get the utmost result, use a soft, fully synthetic brush.

#### Post-painting

Wipe off the tools thoroughly before cleaning with water. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

#### Maintenance

Use a damp cloth and possibly some mild cleaning liquid to clean the surface.