



Product description:

A highly opaque, diffusion-open plaster paint that is colour-durable for façades and plaster bases, concrete and Eternit.

Allows the substrate to breathe and reduces risk of frost-wedging.

N.B! New plaster must dry for 4-6 weeks prior to painting. Do not paint on sun-drenched surfaces or late in the day when there is risk of dew. Can be used on surfaces previously coated with silicate paints.

TECHNICAL DATA:

PARAMETER	VALUE	UNIT	METHOD
Area of application	Out-/Indoors		
Binder	Acrylic/silane mod.		
Volume Solids	40%		
Weight Solids	58%		
Density	1,44	kg/l	
Gloss	3 (fully matt)		
Washability	Class 1 (EN 13300)		
Thinner/Cleaning	Water		
Material consumption	4–8 m ² /L		
Temperature at painting	Minimum +5°C		
Tools for painting	Brush, roller and spray		
Dust dry	1 h		
Re-paintable	2–4 h		
Completely dry	24 h		
Shelf life	2 years if unopened, frost free storage		
Colour	A- and C-base		
Flammability	Not flammable		
VOC category	(Cat A/c): 40 g/l (2010)		
Vapor diffusion	0,13m (Class V2)	Sd (m)	ISO 7783
Water permeability	0,009kg (Class W3)	kg/(m ² ·h0.5)	SS EN 1062 3



Instruction for use:

Mix thoroughly.

Unpainted plaster and concrete:

1. Brush off loose particles. Repair cracks and holes.
2. Apply Betosil with minimum two coats.

Previously painted surfaces:

1. Remove loose plaster/paint. Repair cracks and holes. Wash with Façade Wash (remember to protect the windows). Rinse with water. Let dry completely.
2. Apply Betosil once or twice.