



Declaration of Performance

Betosil

Unique ID-code for type of product:	Betosil
Building product's intended use:	A highly covering, dirt-repellent, permeable and highly weatherproof wall paint for concrete surfaces. See product sheet for more information
Name of manufacturer:	Hagmans Nordic AB Förläggarevägen 2, Box 112 511 10 Fritsla Sweden
The system or systems for the assessment and continuous control of the building product's performance, according to appendix V:	System 4
In those cases where the declaration of performance is for a building product embodied by a harmonized standard:	Tests has issued under the AVCP system 4 for EN1504-2:2004: -Permeability to water vapour according to EN ISO 7783. -Capillary absorption and permeability to water according to EN 1062-3. -Adhesion strength according to EN 1542.

Declared performance

Important properties	Performance	Test Standard	Harmonized technical specification
Permeability to water vapour	Class I	EN ISO 7783	EN 1504-2:2004
Capillary absorption and permeability to water	$w < 0,1 \text{ kg/m}^2\text{h}^{0,5}$	EN 1062-3	
Adhesion strength	$>1,0 \text{ N/mm}^2$	EN 1542	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed by the manufacturer of:

Camilla Eliasson, R&D Manager-Fritsla
Fritsla, 2023-04-17